

Product Summary

VDS (V)	RDS(on),max (mΩ)	ID (A)
-60	200 @ VGS = -10V	-1.8

Features

- ❖ Fast Switching
- ❖ Low On-Resistance
- ❖ Low Gate Charge

Application

- ❖ Load Switch
- ❖ Motor Control
- ❖ Power Management


General Information

Shipping


- ❖ One shipping options is offered as standard
- ❖ Un-sawn wafer

Handling

- ❖ Product must be handled only at ESD safe workstations. Standard ESD precautions and safe work environments are as defined in MIL-HDBK-263.
- ❖ Product must be handled only in a class 10,000 or better-designated clean room environmen




SOT-23



PIN Configuration
(Top View)

Equivalent circuit



Absolute Maximum Rating (Ta=25°C)

Parameter		Symbol	Limit	Unit
Drain-source voltage		V _{DS}	-60	V
Gate-source voltage		V _{GS}	±20	
Continuous drain current (V _{GS} =-4.5V) ⁽¹⁾	T _A =25°C	I _D	-1.8	A
	T _A =70°C		-1.38	
Pulsed drain current ⁽²⁾		I _{D,pulse}	-7.2	
Power dissipation	T _A =25°C	P _D	1.2	W
Operating junction and storage temperature range		T _J , T _{stg}	-55 to 150	°C

**Electrical characteristics (Ta=25°C ± 3°C)**

Parameter	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Static parameter ⁽⁴⁾						
Drain to source breakdown voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = -250 μA	-60			V
Gate-source threshold voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250 μA	-1.1	-1.6	-2.2	V
Gate-body leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±12 V			±100	nA
Zero gate voltage drain current	I _{DSS}	V _{DS} = -60 V, V _{GS} = 0 V			-1	μA
Drain-source on-resistance	R _{DS(on)}	V _{GS} = -10V, I _D = -1.5 A		155	200	mΩ
		V _{GS} = -4.5V, I _D = -1 A		195	252	mΩ
Forward transconductance ⁽⁵⁾	g _{fs}	V _{DS} = -10V, I _D = -1A		4.0		S
Dynamic ⁽⁵⁾						
Total gate charge	Q _g	V _{DS} = -30V, I _D = -1.5A V _{GS} = -10V		9.5		nC
Gate-source charge	Q _{gs}			1.5		
Gate-drain charge	Q _{gd}			2		
Turn-on delay time	t _{d(on)}	V _{GS} = -10V, V _{DD} = -30V I _D = -1.5A, R _{GEN} = 3.0Ω		45		ns
Rise time	t _r			33		
Turn-off delay time	t _{d(off)}			15		
Fall time	t _f			11		
Input capacitance	C _{iss}	V _{DS} = -25 V, V _{GS} = 0 V, f = 1 MHz		533		pF
Output capacitance	C _{oss}			29		
Reverse transfer capacitance	C _{rss}			23		
Reverse Diode Characteristics ⁽⁵⁾						
Diode forward voltage	V _{SD}	I _S = -2.0A, V _{GS} = 0V		-0.8	-1.2	V
Diode Forward Current	I _s	T _A = 25°C			-1.8	A

Notes

1. This current is chip limited, which is calculated based on R_{thjc} .
2. This current is calculated on single pulse with 10μs Pulse & Duty Cycle = 1%.
3. Device mounted on FR-4 substrate PC board with 2oz copper in 1inch square cooling area.
4. Short duration pulse test used to minimize self-heating effect.
5. Defined by design, not subject to production.

Thermal Characteristic (Ta=25°C)

Parameter	Symbol	Typ.	Max.	Unit
Thermal Resistance, Junction-to-Ambient ⁽³⁾	$R_{\theta JA}$	-	104	°C/W

Electrical characteristics diagrams




Fig.1 Typical Output Characteristics




Fig.2 On-Resistance v.s Gate-Source




Fig.3 Forward Characteristics Of Reverse




Fig.4 Gate-Charge Characteristics




Fig.5 Normalized $V_{GS(th)}$ v.s T_J




Fig.6 Normalized $R_{DS(on)}$ v.s T_J

Electrical characteristics diagrams




Fig.7 Capacitance




Fig.8 Safe Operating Area




Fig.9 Normalized Maximum Transient Thermal Impedance




Fig.10 Switching time waveform





Fig.11 Gate Charge waveform

Package outline dimensions SOT-23


Symbol	Dimensions in Millimeters	
	MIN.	MAX.
A	0.90	1.150
A1	0.0	0.100
A2	0.9	1.050
b	0.30	0.500
c	0.08	0.150
D	2.80	3.000
E	1.20	1.400
E1	2.2	2.550
e	0.950 TYP	
e1	1.8	2.000
L	0.55 REF	
L1	0.3	0.500
θ	0°	8°

Notes

1. All dimensions are in millimeters.
2. Tolerance $\pm 0.10\text{mm}$ (4 mil) unless otherwise specified.
3. Package body sizes exclude mold flash and gate burrs. Mold flash at the non-lead sides should be less than 5 mils.
4. Dimension L is measured in gauge plane.
5. Controlling dimension is millimeter, converted inch dimensions are not necessarily exact.

Important Notice

The information given in this document shall be for illustrative purposes only and shall in no event be regarded as a guarantee of conditions or characteristics. Gostone reserves the right to change any information herein. With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Gostone or its affiliates hereby make no representation or warranty of any kind, expressed or implied, as to any information provided hereunder, including without limitation as to the accuracy, completeness or non-infringement of intellectual property rights of any third party, and they assume no liability for the consequences of use of such information. In addition, any information given in this document is subject to customer's compliance with its obligations stated herein and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Gostone in customer's applications. The information contained herein is exclusively intended for technically trained staff. No license is granted by implication under any patent right, copyright, mask work right, or other intellectual property right. It is customer's sole responsibility to evaluate the suitability of the product for the intended application and the completeness of the product information given herein with respect to such application. In no event shall Gostone or its affiliates be liable to any party for any direct, indirect, special, punitive, incidental or consequential damages of any nature whatsoever, including but not limited to loss of profits and loss of goodwill, whether or not such damages are based on tort or negligence, warranty, breach of contract or any other legal theory. In addition, any recipient of this document and the relevant products samples may not alter, decompile, disassemble, reverse engineer, or otherwise modify any information/samples received hereunder. Any intellectual property rights arising from the reverse engineering of Gostone's products shall belong to Gostone.