

N-channel Power MOSFET:
30V, 2.5mohm, 67A

Product Summary

VDSS	VGSS	RDS(ON) TYP/MAX	ID MAX
30V	± 20V	2.7/3.5 mΩ@VGS=10V 4.2/7.4 mΩ@VGS=4.5V	67A

Marking Symbol Code

- ❖ Laser Marking Device Code: AEM



GS : Gostone (fixed)
AEM: Marking Device Code (fixed)
A: Factory Code
Y: Year Code
WW: Week Code
LT: LOT Code
o : Pin#1 Identifier

Form

- ❖ Tape & Reel Embossed Type: 5,000pcs / reel


Features

- ❖ Low RDSon
- ❖ Low Gate Charge
- ❖ High Current Capacity
- ❖ Halogen-Free / RoHS Compliant

Application

- ❖ Battery Charging & Discharging for NB Battery Pack
- ❖ DC/DC Converters in Computing.

Equivalent circuit



Absolute Maximum Rating Ta=25°C

Parameter	Symbol	Rating	Unit
Drain to Source Voltage	VDS	30	V
Gate to Source Voltage	VGS	±20	V
Continuous Drain Current	IDS	67	A
		43	A
Pulsed Drain Current*1	IDM	136	A
Continuous Drain Current	IDS	17	A
		14	A
Avalanche Current	IAS	24	A
Avalanche Energy	EAS	28.5	mJ
Power Dissipation	PD	33	W
		13	W
Power Dissipation*3	PDSM	5.0	W
		3.2	W
Junction Temperature	Tj	150	°C
Storage Temperature	Tstg	-55 to +150	°C

*1Pulse width limited by maximum junction temperature.


*2The value of RθJA is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with Ta=25°C.

*3The Power dissipation is based on RθJA t ≤ 10s value.


Thermal Characteristics (Typical)

Parameter	Symbol	Rating	Unit
Junction-to Ambient (T _A =25°C)			
t ≤ 10s	R _{thJA} ^{*2}	20	°C/W
Steady-State		50	°C/W
Junction-to Case (T _C =25°C)			
Steady-State	R _{thJC}	2.9	°C/W

Top View



Bottom View



1,2,3: Source
4: Gate
5,6,7,8: Drain



Electrical Characteristics (Tj=25degC)


Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	VDSS	ID=250μA, VGS=0V	30			V
Zero Gate Voltage Drain Current	IDSS	VDS=24V, VGS=0V			1	μA
Gate-Source Leakage Current	IGSS	VGS=±20V, VDS=0V			±100	nA
Gate-Source Threshold Voltage	Vth	VDS=VGS, ID=250μA	1.2	1.7	2.4	V
Drain-Source On-State Resistance	RDS(on)1	ID=13A, VGS=10V		2.7	3.5	mΩ
	RDS(on)2	ID=13A, VGS=4.5V		4.2	7.4	
Forward Transconductance	gFS	VGS=5V, ID=13A		61		S
Input Capacitance *1	Ciss	VDS=15V, VGS=0V, f=1MHz		1,100		pF
Output Capacitance *1	Coss			860		
Reverse Transfer Capacitance *1	Crss			37		
Gate Resistance *1	Rg	f=1MHz		3.2		Ω
Turn-On Delay Time *1 *2	td(on)	VDD=15V, VGS=10V, ID=13A		6.8		ns
Rise Time *1 *2	tr			9.8		
Turn-Off Delay Time *1 *2	td(off)	VDD=15V, VGS=10V, ID=13A		30		ns
Fall Time *1 *2	tf			11.5		
Total Gate Charge *1	Qg	VDD=15V, VGS=10V, ID=13A		18		nC
Gate-Source Charge *1	Qgs			3.3		
Gate-Drain Charge *1	Qgd			3.0		
Diode Forward Voltage	VSD	IS=13A, VGS=0V			1.2	V
Maximum Body Diode Continuous Current	IS				26	A
Body Diode Reverse Recovery Time *1	trr	IF=13A, di/dt=100A/μs		19.0		ns
Body Diode Reverse Recovery Charge *1	Qrr			7.7		nC

Note *1 Guaranteed by Design


Note *2 Measurement Circuit for Switching Characteristics

Test circuits


Test Circuit 1
VDSS/IDSS




Test Circuit 2
IGSS




Test Circuit 3
Vth

















Test Circuit 4
RDS(on)










Test Circuit 5
VF




Test circuits
Test Circuit 6
Q_g

Test Circuit 7
Switching Time

Test Circuit 8
IAS

Test Circuit 9
trr/Qrr


Technical data
ID to VDS

ID to VGS

RDS(on) to ID

On-Resistance vs Junction Temperature

RDS(on) to VGS

IF to VF


Technical data
Gate-Charge Characteristics

Capacitance Characteristic

SOA

Single Pulse Maximum Power Dissipation

Thermal Response

Power Derating


Package Outline Dimensions
Top View

Side View


Bottom View


Symbol	Dimensions In Millimeters		
	MIN	NOM	MAX
A	0.900	0.950	1.000
B	0.480	0.580	0.680
B1	0.550	0.650	0.750
C	0.200	0.254	0.300
D	5.100	5.200	5.300
D1	-	-	0.150
E	5.900	6.050	6.200
E1	5.400	5.550	5.700
e	1.220	1.270	1.320
F	0.250	0.300	0.350
H	3.270	3.470	3.670
L	3.800	4.000	4.200
K	1.200	-	-


Form

- ❖ Tape & Reel Embossed Type: 5,000pcs / reel
- ❖ Factory PKG Code: PDFN
- ❖ Tape Width: 12mm, Pitch: 8mm, Reel Size: 12inch


Tape size (mm)



Pin1 Direction



Tape end ~ Leader part (mm)



Important Notice

The information given in this document shall be for illustrative purposes only and shall in no event be regarded as a guarantee of conditions or characteristics. Gostone reserves the right to change any information herein. With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Gostone or its affiliates hereby make no representation or warranty of any kind, expressed or implied, as to any information provided hereunder, including without limitation as to the accuracy, completeness or non-infringement of intellectual property rights of any third party, and they assume no liability for the consequences of use of such information. In addition, any information given in this document is subject to customer's compliance with its obligations stated herein and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Gostone in customer's applications. The information contained herein is exclusively intended for technically trained staff. No license is granted by implication under any patent right, copyright, mask work right, or other intellectual property right. It is customer's sole responsibility to evaluate the suitability of the product for the intended application and the completeness of the product information given herein with respect to such application. In no event shall Gostone or its affiliates be liable to any party for any direct, indirect, special, punitive, incidental or consequential damages of any nature whatsoever, including but not limited to loss of profits and loss of goodwill, whether or not such damages are based on tort or negligence, warranty, breach of contract or any other legal theory. In addition, any recipient of this document and the relevant products samples may not alter, decompile, disassemble, reverse engineer, or otherwise modify any information/samples received hereunder. Any intellectual property rights arising from the reverse engineering of Gostone's products shall belong to Gostone.