


N-channel Power MOSFET:
30V, 3.3mohm, 54A

Product Summary

VDSS	VGSS	RDS(ON) TYP/MAX	ID MAX
30V	± 20V	3.5/4.4 mΩ@VGS=10V 5.7/8.3 mΩ@VGS=4.5V	52A

Marking Symbol Code

- ❖ Laser Marking Device Code: AVM



GS : Gostone (fixed)
AVM Marking Device Code (fixed)
A: Factory Code
Y: Year Code
WW: Week Code
LT: LOT Code
● : Pin#1 Identifier

Form

- ❖ Tape & Reel Embossed Type: 5,000pcs / reel

Absolute Maximum Rating Ta=25°C


Parameter	Symbol	Rating	Unit
Drain to Source Voltage	VDS	30	V
Gate to Source Voltage	VGS	±20	V
Continuous Drain Current	IDM	52	A
		33	A
Pulsed Drain Current*1	IDM	104	A
Continuous Drain Current	IDSM	14.8	A
		11.7	A
Avalanche Current	IAS	21	A
Avalanche Energy	EAS	22	mJ
Power Dissipation	PD	26	W
		10	W
Power Dissipation*3	PD _{SM}	4.9	W
		3.1	W
Junction Temperature	Tj	150	°C
Storage Temperature	Tstg	-55 to +150	°C

*1Pulse width limited by maximum junction temperature.


*2The value of R_{θJA} is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C.

*3The Power dissipation is based on R_{θJA} t ≤ 10s value.

Top View



Bottom View



1,2,3: Source
4: Gate
5,6,7,8: Drain


Features

- ❖ Low RDSon
- ❖ Low Gate Charge
- ❖ High Current Capacity
- ❖ Halogen-Free / RoHS Compliant

Application

- ❖ Battery Charging & Discharging for NB Battery Pack
- ❖ DC/DC Converters in Computing.

Equivalent circuit



Thermal Characteristics (Typical)

Parameter	Symbol	TYP	Unit
Junction-to Ambient (T _A =25°C)			
t ≤ 10s	RthJA*2	20.4	°C/W
Steady-State		52.8	°C/W
Junction-to Case (Tc=25°C)			
Steady-State	RthJC	3.7	°C/W

Electrical Characteristics (Tj=25degC)


Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	VDSS	ID=250μA, VGS=0V	30			V
Zero Gate Voltage Drain Current	IDSS	VDS=24V, VGS=0V			1	μA
Gate-Source Leakage Current	IGSS	VGS=±20V, VDS=0V			±100	nA
Gate-Source Threshold Voltage	Vth	VDS=VGS, ID=250μA	1.2	1.6	2.4	V
Drain-Source On-State Resistance	RDS(on)1	ID=13A, VGS=10V		3.5	4.4	mΩ
	RDS(on)2	ID=13A, VGS=4.5V		5.7	8.3	
Forward Transconductance	gFS	VGS=5V, ID=13A		74		S
Input Capacitance *1	Ciss	VDS=15V, VGS=0V, f=1MHz		980		pF
Output Capacitance *1	Coss			750		
Reverse Transfer Capacitance *1	Crss			36		
Gate Resistance *1	Rg	f=1MHz		2.0		Ω
Turn-On Delay Time *1 *2	td(on)	VDD=15V, VGS=10V, ID=13A		8.8		ns
Rise Time *1 *2	tr			4.9		
Turn-Off Delay Time *1 *2	td(off)	VDD=15V, VGS=10V, ID=13A		21.0		ns
Fall Time *1 *2	tf			6.6		
Total Gate Charge *1	Qg	VDD=15V, VGS=10V, ID=13A		18.8		nC
Gate-Source Charge *1	Qgs			2.7		
Gate-Drain Charge *1	Qgd			4.3		
Diode Forward Voltage	VSD	IS=13A, VGS=0V			1.2	V
Maximum Body Diode Continuous Current	IS				21.5	A
Body Diode Reverse Recovery Time *1	trr	IF=13A, di/dt=100A/μs		37		ns
Body Diode Reverse Recovery Charge *1	Qrr			39		nC

Note *1 Guaranteed by Design


Note *2 Measurement Circuit for Switching Characteristics

Test circuits


Test Circuit 1
VDSS/IDSS




Test Circuit 2
IGSS




Test Circuit 3
Vth

















Test Circuit 4
RDS(on)












Test Circuit 5
VF



Test circuits
**Test Circuit 6
Qg**

**Test Circuit 7
Switching Tin**

**Test Circuit 8
IAS**

**Test Circuit 9
trr/Qrr**


Technical data
ID to VDS

ID to VGS

RDS(on) to ID

On-Resistance vs Junction Temperature

RDS(on) to VGS

IF to VF


Technical data
Gate-Charge Characteristics

Capacitance Characteristic

SOA

Single Pulse Maximum Power Dissipation

Thermal Response

Power Derating



Package Outline Dimensions
Top View

Side View

Bottom View


Symbol	Dimensions In Millimeters		
	MIN	NOM	MAX
A	0.950	1.000	1.050
b	0.250	0.300	0.350
b1	0.300	0.400	0.500
c	0.200	0.250	0.300
D	5.15 BSC		
D1	4.900	5.000	5.100
D2	3.900	4.010	4.200
e	1.170	1.270	1.370
E	6.15 BSC		
E1	5.750	5.850	5.950
E2	3.350	3.500	3.650
H	0.510	0.610	0.710
K	1.100	1.350	1.500
L	0.510	0.610	0.710
L1	0.060	0.130	0.200
L2	-	-	0.120
N	0.400	0.500	0.600
P	0.950	1.100	1.250
θ	9	11	13


Form

- ❖ Tape & Reel Embossed Type: 5,000pcs / reel
- ❖ Factory PKG Code: PDFN
- ❖ Tape Width: 12mm, Pitch: 8mm, Reel Size: 12inch


Tape size (mm)



Pin1 Direction



Tape end ~ Leader part (mm)



Important Notice

The information given in this document shall be for illustrative purposes only and shall in no event be regarded as a guarantee of conditions or characteristics. Gostone reserves the right to change any information herein. With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Gostone or its affiliates hereby make no representation or warranty of any kind, expressed or implied, as to any information provided hereunder, including without limitation as to the accuracy, completeness or non-infringement of intellectual property rights of any third party, and they assume no liability for the consequences of use of such information. In addition, any information given in this document is subject to customer's compliance with its obligations stated herein and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Gostone in customer's applications. The information contained herein is exclusively intended for technically trained staff. No license is granted by implication under any patent right, copyright, mask work right, or other intellectual property right. It is customer's sole responsibility to evaluate the suitability of the product for the intended application and the completeness of the product information given herein with respect to such application. In no event shall Gostone or its affiliates be liable to any party for any direct, indirect, special, punitive, incidental or consequential damages of any nature whatsoever, including but not limited to loss of profits and loss of goodwill, whether or not such damages are based on tort or negligence, warranty, breach of contract or any other legal theory. In addition, any recipient of this document and the relevant products samples may not alter, decompile, disassemble, reverse engineer, or otherwise modify any information/samples received hereunder. Any intellectual property rights arising from the reverse engineering of Gostone's products shall belong to Gostone.