GOSTONE

N-channel Power MOSFET:
30V, 4.2mohm, 44A

RoHS COMPLIANT

GTN3017F

Product Summary			
VDSS	VGSS	RDS(ON) TYP/MAX	ID MAX
30V	± 20V	4.2/5.6 mΩ@VGS=10V 6.7/11 mΩ@VGS=4.5V	**44A**

Features

- Low RDSon
- Low Gate Charge
- High Current Capacity
- Halogen-Free / RoHS Compliant

Application

- Battery Charging & Discharging for NB Battery Pack
- DC/DC Converters in Computing.


Marking Symbol Code

- Laser Marking Device Code: APR



GS : Gostone (fixed)
APR: Marking Device Code (fixed)
A: Factory Code
Y: Year Code
WW: Week Code
LT: LOT Code
○ : Pin#1 Identifier

Equivalent circuit



Form


- Tape & Reel Embossed Type: 5,000pcs / reel

Absolute Maximum Rating Ta=25℃				
Parameter		Symbol	Rating	Unit
Drain to Source Voltage		VDS	30	V
Gate to Source Voltage		VGS	±20	V
Continuous Drain Current	Tc=25°C	IDM	44	A
	Tc=100°C		28	A
Pulsed Drain Current *1		IDM	88	A
Continuous Drain Current	T_A=25°C	IDSM	13	A
	T_A=70°C		10	A
Avalanche Current		IAS	18	A
Avalanche Energy	L=0.1mH	EAS	16.2	mJ
Power Dissipation	Tc=25°C	PD	22.4	W
	Tc=100°C		8.9	W
Power Dissipation *3	T_A=25°C	PDSM	4.2	W
	T_A=70°C		2.7	W
Junction Temperature		Tj	150	℃
Storage Temperature		Tstg	-55 to +150	℃


Thermal Characteristics (Typical)				
Parameter		Symbol	TYP	Unit
Junction-to Ambient (T_A=25°C)				
	t ≤ 10s	R_{thJA} *2	24.0	℃/W
	Steady-State		57.0	℃/W
Junction-to Case (Tc=25°C)				
	Steady-State	R_{thJC}	4.3	℃/W

*1 Pulse width limited by maximum junction temperature.
*2 The value of $R_{\theta JA}$ is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C.
*3 The Power dissipation is based on R_{thJA} t ≤ 10s value.

Top View



Bottom View



1,2,3: Source
4: Gate
5,6,7,8: Drain

Electrical Characteristics (Tj=25degC)


Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	VDSS	ID=250μA, VGS=0V	30			V
Zero Gate Voltage Drain Current	IDSS	VDS=24V, VGS=0V			1	μA
Gate-Source Leakage Current	IGSS	VGS=±20V, VDS=0V			±100	nA
Gate-Source Threshold Voltage	Vth	VDS=VGS, ID=250μA	1.2	1.7	2.4	V
Drain-Source On-State Resistance	RDS(on)1 RDS(on)2	ID=13A, VGS=10V ID=13A, VGS=4.5V		4.2 6.7	5.6 11.0	mΩ
Forward Transconductance	gFS	VGS=5V, ID=13A		78		S
Input Capacitance *1 Output Capacitance *1 Reverse Transfer Capacitance *1	Ciss Coss Crss	VDS=15V, VGS=0V, f=1MHz		792 585 35		pF
Gate Resistance *1	Rg	f=1MHz		5.4		Ω
Turn-On Delay Time *1 *2 Rise Time *1 *2	td(on) tr	VDD=15V, VGS=10V, ID=13A		7 5		ns
Turn-Off Delay Time *1 *2 Fall Time *1 *2	td(off) tf	VDD=15V, VGS=10V, ID=13A		24 10		ns
Total Gate Charge *1 Gate-Source Charge *1 Gate-Drain Charge *1	Qg Qgs Qgd	VDD=15V, VGS=10V, ID=13A		15.4 2.4 3.7		nC
Diode Forward Voltage	VSD	IS=13A, VGS=0V			1.2	V
Maximum Body Diode Continuous Current	IS				18.6	A
Body Diode Reverse Recovery Time *1 Body Diode Reverse Recovery Charge *1	trr Qrr	IF=13A, di/dt=100A/μs		23.0 10.0		ns nC

Note *1 Guaranteed by Design


Note *2 Measurement Circuit for Switching Characteristics

Test circuits


Test Circuit 1
VDSS/IDSS




Test Circuit 2
IGSS




Test Circuit 3
Vth



Test Circuit 4
RDS(on)





Test Circuit 5
VF




Test circuits


Test Circuit 6
Qg







Test Circuit 7
Swiching Tim







Test Circuit 8
IAS






Test Circuit 9
trr/Qrr






Technical data


ID to VDS




ID to VGS




RDS(on) to ID




On-Resistance vs Junction Temperature



RDS(on) to VGS




IF to VF




Technical data


Gate-Charge Characteristics




Capacitance Characteristic




SOA




Single Pulse Maximum Power Dissipation



Thermal Response




Power Derating




Package Outline Dimensions

Top View




Side View





Bottom View




Symbol	Min	Typ	Max
A	0.725	0.775	0.825
B	0.28	0.38	0.48
C	0.13	0.15	0.20
D	3.05	3.15	3.25
D1			0.10
E	3.25	3.35	3.45
E1	3.0	3.1	3.2
e	0.60	0.65	0.70
F	0.25	0.30	0.35
H	1.48	1.58	1.68
L	2.35	2.45	2.55


Form

- Tape & Reel Embossed Type: 5,000pcs / reel
- Factory PKG Code: PDFN
- Tape Width: 12mm, Pitch: 8mm, Reel Size: 12inch


Tape size (mm)



Pin1 Direction



Tape end ~ Leader part (mm)



Important Notice

The information given in this document shall be for illustrative purposes only and shall in no event be regarded as a guarantee of conditions or characteristics. Gostone reserves the right to change any information herein. With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Gostone or its affiliates hereby make no representation or warranty of any kind, expressed or implied, as to any information provided hereunder, including without limitation as to the accuracy, completeness or non-infringement of intellectual property rights of any third party, and they assume no liability for the consequences of use of such information. In addition, any information given in this document is subject to customer's compliance with its obligations stated herein and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Gostone in customer's applications. The information contained herein is exclusively intended for technically trained staff. No license is granted by implication under any patent right, copyright, mask work right, or other intellectual property right. It is customer's sole responsibility to evaluate the suitability of the product for the intended application and the completeness of the product information given herein with respect to such application. In no event shall Gostone or its affiliates be liable to any party for any direct, indirect, special, punitive, incidental or consequential damages of any nature whatsoever, including but not limited to loss of profits and loss of goodwill, whether or not such damages are based on tort or negligence, warranty, breach of contract or any other legal theory. In addition, any recipient of this document and the relevant products samples may not alter, decompile, disassemble, reverse engineer, or otherwise modify any information/samples received hereunder. Any intellectual property rights arising from the reverse engineering of Gostone's products shall belong to Gostone.